



Licence Details			
Number:	3925		
Anniversary Date:	01-October		
Licensee			
ESSENTIAL ENERGY			
PO BOX 718			
QUEANBEYAN NSW 262	20		
	-		
Licence Type			
Premises			
Duraniana			
Premises	WATER TREATMENT PLANT		
WILLS STREET WASTE	WATER TREATMENT FLANT		
BROKEN HILL NSW 288	0		
BROKEN HEE NOW 200	5		
Scheduled Activity			
Sewage treatment			
Fee Based Activity		Scale	
	sing by small plants (< 10000 ML p		1L discharged
			<u> </u>
<u>Region</u>			
South - Griffith			
	n City Plaza, 130-140 Banna Av	renue	
GRIFFITH NSW 2680			
Phone: 02 6969 0700			
Fax: 02 6969 0710			
PO Box 397 GRIFFITH			
NSW 2680			



Licence - 3925

INFC	ORMATION ABOUT THIS LICENCE	4
	ictionary	
	esponsibilities of licensee	
Va	ariation of licence conditions	4
D	uration of licence	4
	cence review	
	ees and annual return to be sent to the EPA	
	ransfer of licence	
Ρι	ublic register and access to monitoring data	
1	ADMINISTRATIVE CONDITIONS	
A	5	
A2		
A		
A		
A	5 Objectives of this licence	7
2	DISCHARGES TO AIR AND WATER AND APPLICATIONS TO LAND	
P		
3	LIMIT CONDITIONS	
L1		
L2		
L3		
L4	4 Volume and mass limits	. 12
L5		
Le		
L7		
L٤		
4	OPERATING CONDITIONS	
0		
0		
0		
04		
0	5	
0		
0	5 1 1 5	
0	,	
0		
	10 Retention of Utilisation Area	
5	MONITORING AND RECORDING CONDITIONS	
Μ	11 Monitoring records	. 16



Licence - 3925

M2	Requirement to monitor concentration of pollutants discharged	
M3	Testing methods - concentration limits	
M4	Recording of pollution complaints	
M5	Telephone complaints line	
M6	Requirement to monitor volume or mass	
M7	Requirement to record sewage treatment plant bypasses	
M8	Biosolids monitoring	
M9	Requirement to record overflows	
M1	0 Environmental monitoring	
6	REPORTING CONDITIONS	
R1	Annual return documents	
R2	Notification of environmental harm	
R3	Written report	
R4	Notification of bypass or overflow incidents	
R5	Annual System Performance Report	
GENE	ERAL CONDITIONS	
G1	Copy of licence kept at the premises	
G2	Signage	
G3	Contact number for incidents and responsible employees	
G4	Clean-up	
Poll	UTION STUDIES AND REDUCTION PROGRAMS	
SPEC	IAL CONDITIONS	
DICTI	ONARY	
Ge	neral Dictionary	
Spe	ecial Dictionary	

Licence - 3925



Information about this licence

Dictionary

A definition of terms used in the licence can be found in the dictionary at the end of this licence.

Responsibilities of licensee

Separate to the requirements of this licence, general obligations of licensees are set out in the Protection of the Environment Operations Act 1997 ("the Act") and the Regulations made under the Act. These include obligations to:

- ensure persons associated with you comply with this licence, as set out in section 64 of the Act;
- control the pollution of waters and the pollution of air (see for example sections 120 132 of the Act); and
- report incidents causing or threatening material environmental harm to the environment, as set out in Part 5.7 of the Act.

Variation of licence conditions

The licence holder can apply to vary the conditions of this licence. An application form for this purpose is available from the EPA.

The EPA may also vary the conditions of the licence at any time by written notice without an application being made.

Where a licence has been granted in relation to development which was assessed under the Environmental Planning and Assessment Act 1979 in accordance with the procedures applying to integrated development, the EPA may not impose conditions which are inconsistent with the development consent conditions until the licence is first reviewed under Part 3.6 of the Act.

Duration of licence

This licence will remain in force until the licence is surrendered by the licence holder or until it is suspended or revoked by the EPA or the Minister. A licence may only be surrendered with the written approval of the EPA.

Licence review

The Act requires that the EPA review your licence at least every 5 years after the issue of the licence, as set out in Part 3.6 and Schedule 5 of the Act. You will receive advance notice of the licence review.

Fees and annual return to be sent to the EPA

For each licence fee period you must pay:

- an administrative fee; and
- a load-based fee (if applicable).

The EPA publication "A Guide to Licensing" contains information about how to calculate your licence fees.





The licence requires that an Annual Return, comprising a Statement of Compliance and a summary of any monitoring required by the licence (including the recording of complaints), be submitted to the EPA. The Annual Return must be submitted within 60 days after the end of each reporting period. See condition R1 regarding the Annual Return reporting requirements.

Usually the licence fee period is the same as the reporting period.

Transfer of licence

The licence holder can apply to transfer the licence to another person. An application form for this purpose is available from the EPA.

Public register and access to monitoring data

Part 9.5 of the Act requires the EPA to keep a public register of details and decisions of the EPA in relation to, for example:

- licence applications;
- licence conditions and variations;
- statements of compliance;
- load based licensing information; and
- load reduction agreements.

Under s320 of the Act application can be made to the EPA for access to monitoring data which has been submitted to the EPA by licensees.

This licence is issued to:

ESSENTIAL ENERGY PO BOX 718 QUEANBEYAN NSW 2620

subject to the conditions which follow.

1 Administrative conditions

A1 What the licence authorises and regulates

- A1.1 Not applicable.
- A1.2 This licence authorises the carrying out of the scheduled activities listed below at the premises specified in A2. The activities are listed according to their scheduled activity classification, feebased activity classification and the scale of the operation.



Licence - 3925

Unless otherwise further restricted by a condition of this licence, the scale at which the activity is carried out must not exceed the maximum scale specified in this condition.

Scheduled Activity

Sewage treatment

Scale
> 1000 - 5000 ML discharged

A1.3 Not applicable.

Licence - 3925



A2 Premises to which this licence applies

A2.1 The licence applies to the following premises:

Premises Details
WILLS STREET WASTEWATER TREATMENT
PLANT
WILLS STREET
BROKEN HILL
NSW
2880
LOT 100 DP 1136508

- A2.2 The premises also includes the reticulation system owned and operated by the licensee that is associated with the sewage treatment plant(s) identified in condition A2.1.
- A2.3 The premises also includes the utilisation area located at E 540753 N 6462038.

A3 Other activities

A3.1 Not applicable.

A4 Information supplied to the EPA

A4.1 Works and activities must be carried out in accordance with the proposal contained in the licence application, except as expressly provided by a condition of this licence.

In this condition the reference to "the licence application" includes a reference to:

- (a) the applications for any licences (including former pollution control approvals) which this licence replaces under the Protection of the Environment Operations (Savings and Transitional) Regulation 1998; and
- (b) the licence information form provided by the licensee to the EPA to assist the EPA in connection with the issuing of this licence.

A5 Objectives of this licence

Licence - 3925



- A5.1 The objectives of this licence are to:
 - (a) prevent as far as practicable sewage overflows and sewage treatment plant bypasses;
 - (b) require proper and efficient management of the system to minimise harm to the environment and public health; and
 - (c) require practical measures to be taken to protect the environment and public health from sewage overflows and sewage treatment plant effluent.
- A5.2 This licence is to be construed in a manner that will promote the objectives referred to in A5.1.

2 Discharges to air and water and applications to land

P1 Location of monitoring/discharge points and areas

- P1.1 Not applicable.
- P1.2 The following points referred to in the table are identified in this licence for the purposes of the monitoring and/or the setting of limits for discharges of pollutants to water from the point.
- P1.3 The following utilisation areas referred to in the table below are identified in this licence for the purposes of the monitoring and/or the setting of limits for any application of solids or liquids to the utilisation area.

Licence - 3925



Water and land

EPA identi-	Type of monitoring point	Type of discharge point	Description of location
fication no.			
1		Discharge to waters	The discharge to the open drain at the end of the outfall pipeline adjacent to Pinnacles Road as shown on map "Broken Hill Water Board Sewerage Treatment Plant & Discharge Point" dated 27/8/99 on EPA file 235007A2.
2	Volume monitoring	Volume monitoring	Flowmeter at the effluent flume (for discharge point 1) shown as Final Monitor Point E 540931 N 6461814 on countrywater Drawing No 375/1 dated 2/06/2010 on EPA file LIC/2540.
3		Discharge to land	Pipe discharge to tank at Perilya South Mine E 541265 N 6461208; Pipe shown as "To Pasminco" on countrywater Drawing No 375/1 dated 2/06/2010 and on EPA file LIC07/2540.
4	Volume monitoring		Flowmeters on pipe (for discharge point 3) adjacent to Pasminco Pump Station & Compound shown on countrywater Drawing No 375/1 dated 2/06/2010 on EPA file LIC07/2540.
5		Discharge to land	Pipe discharge to dam at BH North Golf Club; E 545256 N 6469226 shown as "Golf Club Pipe Line" on countrywater Drawing No 375/1 dated 2/06/2010 on EPA file LIC/2540.
6	Effluent quality monitoring	Effluent quality monitoring	Final Sample Point E 540897 N6461814 (for discharge points 1, 3, 5, 7, 11, 12, 13, 14 & 15) shown on countrywater Drawing No 375/1 dated 2/06/2010 on EPA file LIC07/2540.

Licence - 3925



EPA identi-	Type of monitoring point	Type of discharge point	Description of location
fication no.			
7	Discharge to utilisation	Discharge to utilisation area	Pipe discharge and meter to utilisation area
	area		shown as "Effluent Internal Reuse Meter E
			540753 N 6462038" on countrywater Drawing
			No 375/1 dated 2/06/2010 on EPA file
			LIC07/2540. This pipe is an off-take from the
			golf course pipe (point 5).
10	Volume monitoring		Golf Club Flow Meter E 540888 N 6461814
			(For discharge Point 5) shown on
			countrywater Drawing No 375/1 dated
			2/06/2010 on EPA file LIC072540.
11		Discharge to land	Pipe discharge to tank at Regeneration
			Reserve (Brown Street) E 542010 N 6465671,
			thereafter pumped by BHCC to Living Desert;
			E 541824 N 6469665. This pipe is an off-take
			from golf course pipe (point 5).
12		Discharge to land	Stand-pipe at Broken Hill Racecourse E
			545313 N 6468622. Stand-pipe is an off-take
			from golf course pipe (point 5).
13		Discharge to land	Pipe discharge to tank at Silverlea - Picton
			Plants E 541283 N 6463990. This pipe is an
			off-take from the golf course pipe (point 5).
14		Discharge to land	Pipe to MSP with pipeline crossing Bemax
			boundary at E0538932 N646100. Pipe shown
			as "Bemax Line" on countrywater Drawing No
			375/1 dated 2/06/2010 on EPA file
			LIC07/2540.
15		Discharge to land	Pipe to Tree Area Internal Reuse Line shown
			on countrywater Drawing No 375/1 dated
			2/06/2010 and on EPA file LIC07/2540. This
			pipe is an off-take from the golf course pipe
			(point 5)

Licence - 3925



3 Limit conditions

L1 Pollution of waters

- L1.1 Except as may be expressly provided in any other condition of this licence, the licensee must comply with section 120 of the Protection of the Environment Operations Act 1997.
- L1.2 The licensee may only discharge untreated or partially treated sewage from the sewage treatment plant and/or the reticulation system subject to the conditions of this licence, including O1 and O2.

L2 Load limits

- L2.1 The actual load of an assessable pollutant discharged from the premises during the reporting period must not exceed the load limit specified for the assessable pollutant in the table below.
- Note: An assessable pollutant is a pollutant which affects the licence fee payable for the licence.
- L2.2 The actual load of an assessable pollutant must be calculated in accordance with the relevant load calculation protocol.

Assessable Pollutant	Load limit (kg)
BOD (Enclosed Waters)	14900
Nitrogen (total) (Enclosed Waters)	27558
Oil and Grease (Enclosed Waters)	3300
Phosphorus (total) (Enclosed Waters)	10800
Total suspended solids (Enclosed Waters)	37450

Note: The load limits referred to in condition L2.1 do not apply to discharges from the reticulation system.

L3 Concentration limits

- L3.1 For each monitoring/discharge point or utilisation area specified in the table\s below (by a point number), the concentration of a pollutant discharged at that point, or applied to that area, must not exceed the concentration limits specified for that pollutant in the table.
- L3.2 Where a pH quality limit is specified in the table, the specified percentage of samples must be within the specified ranges.
- L3.3 To avoid any doubt, this condition does not authorise the pollution of waters by any pollutant other

Licence - 3925

Environment, Climate Change & Water

than those specified in the table\s.

Water and Land

POINT 6	6					
	Pollutant	Units of Measure	50 percentile concentration limit	90 percentile concentration limit	3DGM concentration limit	100 percentile Concentration Limit
	Oil and Grease	milligrams per litre				10
	рН	рН				6.5-8.5
	Total suspended solids	milligrams per litre				50
	Biochemical oxygen demand	milligrams per litre				50

- L3.4 When a wet weather bypass is occurring, exceedances of the 3DGM and the 100 percentile concentration limits in L3 are permitted at the following points for the duration of the bypass: Point 6
- L3.5 The licensee is not taken to have exceeded a quality limit specified in this licence for Biochemical oxygen demand, Total suspended solids or pH if:
 - (a) monitoring by the licensee shows that the level of chlorophyll-a in the maturation ponds during any exceedance was 100 ug/L or more (showing the the exceedance was caused by excessive algal growth); and
 - (b) the liquid waste entering the maturation ponds during the exceedance complies with the quality limit.

L4 Volume and mass limits

- L4.1 For each discharge point or utilisation area specified below (by a point number), the volume/mass of:
 - (a) liquids discharged to water; or;
 - (b) solids or liquids applied to the area;

must not exceed the volume/mass limit specified for that discharge point or area.

Point	Unit of measure	Volume/Mass Limit
2	kilolitres per day	18150

L5 Waste



Licence - 3925

- L5.1 The licensee must not cause, permit or allow any waste generated outside the premises to be received at the premises for storage, treatment, processing, reprocessing or disposal or any waste generated at the premises to be disposed of at the premises, except as expressly permitted by the licence.
- L5.2 This condition only applies to the storage, treatment, processing, reprocessing or disposal of waste at the premises if those activities require an environment protection licence.
- L5.3 The licensee may receive and/or transfer sewage and Group C waste generated outside the premises for treatment, processing or reprocessing at the premises. The licensee must take reasonable steps to ensure that sewage received at the premises has been lawfully discharged in accordance with a trade waste agreement or customer contract (as applicable) in force between the licensee and the generator of the waste. The licensee must treat, process or reprocess the sewage and Group C waste in accordance with this licence prior to discharge from the premises.
- L5.4 The licensee may receive, store, treat, process or reprocess and/or transfer at the premises sewage products generated or stored outside the premises by the licensee's other sewage treatment systems. Sewage products must be received, treated, processed or reprocessed in accordance with this licence.
- L6 Noise Limits
- L6.1 Not applicable.
- L7 Frequency limits
- L7.1 Not applicable.

L8 Potentially offensive odour

- L8.1 No condition in this licence identifies a potentially offensive odour for the purposes of section 129 of the Protection of the Environment Operations Act 1997.
- Note: Section 129 of the Protection of the Environment Operations Act 1997 provides that the licensee must not cause or permit the emission of any offensive odour from the premises but provides a defence if the emission is identified in the relevant environment protection licence as a potentially offensive odour and the odour was emitted in accordance with the conditions of a licence directed at minimising odour.

4 **Operating conditions**

Licence - 3925



O1 Activities must be carried out in a competent manner

O1.1 Licensed activities must be carried out in a competent manner.

This includes:

- (a) the processing, handling, movement and storage of materials and substances used to carry out the activity; and
- (b) the treatment, storage, processing, reprocessing, transport and disposal of waste generated by the activity.
- Note: The requirements of O1.1 apply to the whole of the premises, including the reticulation system.

O2 Maintenance of plant and equipment

- O2.1 All plant and equipment installed at the premises or used in connection with the licensed activity: (a) must be maintained in a proper and efficient condition; and
 - (b) must be operated in a proper and efficient manner.
- Note: The requirements of O2.1 apply to the whole of the premises, including the reticulation system.

O3 Appropriate treatment processes

O3.1 Sewage or effluent must not be discharged from Point(s) 1 unless it has been treated in accordance with the requirements of the table below.

Required treatment process	Flow range
Screening, degritting, primary sedimentation, trickling filtration, secondary sedimentation, final ponding and ultra violet disinfection	The portion of sewage inflows that is 95 L/s or less
Screening, degritting, primary sedimentation, trickling filtration, secondary sedimentation and final ponding	The portion of the sewage inflow that is between 95 L/s and 144 L/s
Screening, degritting, primary sedimentation and final ponding	The portion of the sewage inflow that is 144 L/s or more

The flows noted in the table above are the inflows to the premises' sewage treatment plant(s).

O4 **Prohibition on acceptance of pesticides**

- O4.1 The licensee must not consent to the receipt of organochlorine pesticides (including dieldrin, heptachlor and chlordane) into the sewage treatment system after October 2003.
- O4.2 The licensee must not enter into any trade waste agreement to discharge organophosphate pesticides (including chlorpyrifos, diazinon, malathion) into the sewerage system.

O5 Biosolids management



Licence - 3925

- O5.1 Biosolids at the premises must be stored, treated, processed, classified, transported and disposed in accordance with the Biosolids Guidelines, or as otherwise approved in writing by the EPA.
- Note: This condition does not apply to the reuse or disposal of biosolids by the licensee at locations other than the premises.

O6 Effluent application to land

O6.1 The quantity of effluent applied to the utilisation area(s) must not exceed the capacity of the utilisation area(s) to effectively utilise the effluent.

For the purpose of this condition, "effectively utilise" includes the ability of the soil to absorb the nutrient, salt and hydraulic loads and the applied organic material without causing harm to the environment.

- O6.2 Effluent application to the utilisation area(s) must not occur in a manner that causes surface run-off from the utilisation area(s).
- O6.3 Spray from effluent application to the utilisation area(s) must not drift beyond the boundary of the utilisation area(s) to which it has been applied.
- O6.4 Livestock access to any effluent application area must be denied during effluent application and until the applied effluent area has dried.
- O6.5 All effluent application operations and activities occurring at the premises must be carried out in a manner that will minimise dust at the boundary of the utilisation area.
- O6.6 Effluent liquid waste pipelines and fittings must be clearly identified. Standard watertaps, hoses and valves must not be fitted to the pipelines of the effluent system. The effluent system must not be connected to other pipelines. Lockable valves or removable handles must be used where there is public access to the effluent.
- O6.7 Public access to any effluent utilisation area must be denied during effluent application and until the effluent application area has dried.
- O6.8 Adequate notices, warning the public not to drink or otherwise use the treated effluent, must be erected on the site. These notices must be legible English and in any other languages as may be necessary, and must indicate at least that the water in use is "Reclaimed Water Unfit for Drinking".
- O6.9 Liquids must only be applied to liquids utilisation areas for which a discharge point or area has been identified in condition P1.3 of this licence.

O7 New sewage pumping stations

O7.1 Dry weather overflows resulting in pollution of waters from any sewage pumping station(s) installed within the sewage treatment system after January 2004 are not permitted.

Licence - 3925



O8 Extensions to the reticulation system

- O8.1 The licensee must ensure that any extensions to the reticulation system after January 2004 are planned, designed, constructed and installed to prevent as far as practicable overflows from the premises.
- Note: "The premises" includes both the new and the previously existing parts of the sewage treatment system.

O9 Dust Control

O9.1 All operations and activities occurring at the premises must be carried out in a manner that will minimise dust at the boundary of the premises.

O10 Retention of Utilisation Area

- O10.1 The licensee must retain the utilisation area.
- O10.2 At least 14 days prior to a utilisation area being offered for sale, being disposed of or otherwise rendered unavailable for use, the EPA must be must be advised in writing of this intention.

5 Monitoring and recording conditions

M1 Monitoring records

- M1.1 The results of any monitoring required to be conducted by this licence or a load calculation protocol must be recorded and retained as set out in this condition.
- M1.2 All records required to be kept by this licence must be:
 - (a) in a legible form, or in a form that can readily be reduced to a legible form;
 - (b) kept for at least 4 years after the monitoring or event to which they relate took place; and
 - (c) produced in a legible form to any authorised officer of the EPA who asks to see them.
- M1.3 The following records must be kept in respect of any samples required to be collected for the purposes of this licence:
 - (a) the date(s) on which the sample was taken;
 - (b) the time(s) at which the sample was collected;
 - (c) the point at which the sample was taken; and
 - (d) the name of the person who collected the sample.

M2 Requirement to monitor concentration of pollutants discharged



Licence - 3925

M2.1 For each monitoring/discharge point or utilisation area specified below (by a point number), the licensee must monitor (by sampling and obtaining results by analysis) the concentration of each pollutant specified in Column 1. The licensee must use the sampling method, units of measure, and sample at the frequency, specified opposite in the other columns:

Water and Land

		Water and Eand	
Pollutant	Units of measure	Frequency	Sampling Method
Biochemical oxygen demand	milligrams per litre	Special Frequency 1	Special Method 1
Cadmium	milligrams per litre	Quarterly	Representative sample
Lead	milligrams per litre	Quarterly	Representative sample
Nitrate + nitrite (oxidised nitrogen)	milligrams per litre	Special Frequency 1	Special Method 1
Oil and Grease	milligrams per litre	Special Frequency 1	Special Method 1
Phosphorus (total)	milligrams per litre	Special Frequency 1	Special Method 1
Total Kjeldahl Nitrogen	milligrams per litre	Special Frequency 1	Special Method 1
Total dissolved solids	milligrams per litre	Special Frequency 1	Special Method 1
Total suspended solids	milligrams per litre	Special Frequency 1	Special Method 1
рН	pН	Quarterly	Representative sample

For the purposes of the table(s) above Special Frequency 1 means the collection of samples taken twelve (12) times per year at a minimum of 25 days apart.

For the purposes of the table(s) above Special Method 1 means the collection of a composite sample by taking at least three (3) grab samples forming the composite, with the first and last samples taken at least seven (7) hours apart.

M3 Testing methods - concentration limits

- M3.1 Not applicable.
- M3.2 Subject to any express provision to the contrary in this licence, monitoring for the concentration of a pollutant discharged to waters or applied to a utilisation area must be done in accordance with the Approved Methods Publication unless another method has been approved by the EPA in writing before any tests are conducted.

Note: Testing methods - load limit

Note: Clause 18 (1), (1A) and (2) of the Protection of the Environment Operations (General) Regulation 1998 requires that monitoring of actual loads of assessable pollutants listed in L2.1 must be carried out in accordance with the testing method set out in the relevant load calculation protocol for the fee-based activity classification listed in condition A1.2.

Licence - 3925



M4 Recording of pollution complaints

- M4.1 The licensee must keep a legible record of all complaints made to the licensee or any employee or agent of the licensee in relation to pollution arising from any activity to which this licence applies.
- M4.2 The record must include details of the following:
 - (a) the date and time of the complaint;
 - (b) the method by which the complaint was made;
 - (c) any personal details of the complainant which were provided by the complainant or, if no such details were provided, a note to that effect;
 - (d) the nature of the complaint;
 - (e) the action taken by the licensee in relation to the complaint, including any follow-up contact with the complainant; and
 - (f) if no action was taken by the licensee, the reasons why no action was taken.
- M4.3 The record of a complaint must be kept for at least 4 years after the complaint was made.
- M4.4 The record must be produced to any authorised officer of the EPA who asks to see them.

M5 Telephone complaints line

- M5.1 The licensee must operate during its operating hours a telephone complaints line for the purpose of receiving any complaints from members of the public in relation to activities conducted at the premises or by the vehicle or mobile plant, unless otherwise specified in the licence.
- M5.2 The licensee must notify the public of the complaints line telephone number and the fact that it is a complaints line so that the impacted community knows how to make a complaint.
- M5.3 Conditions M5.1 and M5.2 do not apply until 3 months after:
 - (a) the date of the issue of this licence or
 - (b) if this licence is a replacement licence within the meaning of the Protection of the Environment Operations (Savings and Transitional) Regulation 1998, the date on which a copy of the licence was served on the licensee under clause 10 of that regulation.
- M5.4 For the purpose of condition M5.1, operating hours are defined as twenty-four hours a day, seven days a week.
- M5.5 The public notification referred to in condition M5.2 must include specific reference to the fact that the complaints line may be used by the community for the reporting of overflows.

M6 Requirement to monitor volume or mass

M6.1 For each discharge point or utilisation area specified below, the licensee must monitor:

Licence - 3925

- the volume of liquids discharged to water or applied to the area;
- (a) the volume of liquids discharged to wate(b) the mass of solids applied to the area:
- (c) the mass of pollutants emitted to the air;

at the frequency and using the method and units of measure, specified below.

POINT 2

Frequency	Unit Of Measure	Sampling Method
Continuous	kilolitres per day	Level sensor and continuous logger

POINT 10

Frequency	Unit Of Measure	Sampling Method
Continuous	kilolitres per day	Flow meter and continuous logger

- M6.2 In the event that the licensee cannot comply with a volume monitoring method as required by this licence solely due to the failure or malfunction of essential monitoring equipment, volume may be estimated using another agreed method approved in writing by the EPA. This provision only applies for the duration of the failure or malfunction. The licensee is to rectify the failure or malfunction as soon as practicable.
- M6.3 The licensee must:
 - (a) submit in writing to the EPA a proposal for a method of volume estimation; or
 - (b) use a method of volume estimation already approved in writing by the EPA,

to be used in the event that essential monitoring equipment referred to in the previous condition has failed or malfunctioned.

M7 Requirement to record sewage treatment plant bypasses

- M7.1 The licensee must record the following details in respect of each bypass of any of the appropriate treatment processes required by condition O3 which may be reasonably expected to adversely affect the quality of the final discharge:
 - (a) the EPA point identification number through which the bypass discharged;
 - (b) the date, estimated start time and estimated duration of the bypass;
 - (c) the estimated volume of the bypass;
 - (d) the level of treatment of the sewage at the STP prior to discharge;
 - (e) the probable cause of the bypass;
 - (f) any actions taken to stop the bypass happening; and
 - (g) any actions taken to prevent the bypass happening again.
- M7.2 In addition to the details listed in the previous condition, the licensee must also record classification as a wet or dry weather bypass in respect of each bypass referred to in the previous condition. A dry weather bypass is a bypass that occurs when the flow rate of sewage at the inflow volume

Environment, Climate Change



Licence - 3925

monitoring point of the STP does not exceed 18150 kL/day and a wet weather bypass occurs when this flow is equalled or exceeded at any time during the bypass event.

M8 Biosolids monitoring

- M8.1 Biosolids at the premises must be recorded, monitored and classified in accordance with the Biosolids Guidelines, to the extent that those Guidelines are applicable, or as otherwise approved in writing by the EPA.
- Note: This condition does not apply to the reuse or disposal of biosolids by the licensee at locations other than the premises.

M9 Requirement to record overflows

- M9.1 From October 2003 the licensee must record the following details in relation to each observed or reported overflow from the reticulation system and from the sewage treatment plant:
 - (a) the location of the overflow;
 - (b) the date, estimated start time and estimated duration of the overflow;
 - (c) the estimated volume of the overflow;
 - (d) a description of the receiving environment of the overflow;
 - (e) classification as a dry or wet weather overflow;
 - (f) the probable cause of the overflow;
 - (g) any actions taken to stop the overflow happening;
 - (h) any actions taken to clean up the overflow; and
 - (i) any actions taken to prevent the overflow happening again.

M10 Environmental monitoring

M10.1 Not applicable.

6 Reporting conditions

R1 Annual return documents

What documents must an Annual Return contain?

- R1.1 The licensee must complete and supply to the EPA an Annual Return in the approved form comprising:
 - (a) a Statement of Compliance; and
 - (b) a Monitoring and Complaints Summary.

A copy of the form in which the Annual Return must be supplied to the EPA accompanies this licence. Before the end of each reporting period, the EPA will provide to the licensee a copy of the form that must be completed and returned to the EPA.



Licence - 3925

Period covered by Annual Return

- R1.2 An Annual Return must be prepared in respect of each reporting period, except as provided below.
- Note: The term "reporting period" is defined in the dictionary at the end of this licence. Do not complete the Annual Return until after the end of the reporting period.
- R1.3 Where this licence is transferred from the licensee to a new licensee:
 - (a) the transferring licensee must prepare an Annual Return for the period commencing on the first day of the reporting period and ending on the date the application for the transfer of the licence to the new licensee is granted; and
 - (b) the new licensee must prepare an Annual Return for the period commencing on the date the application for the transfer of the licence is granted and ending on the last day of the reporting period.
- Note: An application to transfer a licence must be made in the approved form for this purpose.
- R1.4 Where this licence is surrendered by the licensee or revoked by the EPA or Minister, the licensee must prepare an Annual Return in respect of the period commencing on the first day of the reporting period and ending on:
 - (a) in relation to the surrender of a licence the date when notice in writing of approval of the surrender is given; or
 - (b) in relation to the revocation of the licence the date from which notice revoking the licence operates.

Deadline for Annual Return

R1.5 The Annual Return for the reporting period must be supplied to the EPA by registered post not later than 60 days after the end of each reporting period or in the case of a transferring licence not later than 60 days after the date the transfer was granted (the 'due date').

Notification where actual load can not be calculated

- R1.6 Where the licensee is unable to complete a part of the Annual Return by the due date because the licensee was unable to calculate the actual load of a pollutant due to circumstances beyond the licensee's control, the licensee must notify the EPA in writing as soon as practicable, and in any event not later than the due date. The notification must specify:
 - (a) the assessable pollutants for which the actual load could not be calculated; and
 - (b) the relevant circumstances that were beyond the control of the licensee.

Licensee must retain copy of Annual Return

R1.7 The licensee must retain a copy of the Annual Return supplied to the EPA for a period of at least 4 years after the Annual Return was due to be supplied to the EPA.

Certifying of Statement of Compliance and signing of Monitoring and Complaints Summary

- R1.8 Within the Annual Return, the Statement of Compliance must be certified and the Monitoring and Complaints Summary must be signed by:
 - (a) the licence holder; or
 - (b) by a person approved in writing by the EPA to sign on behalf of the licence holder.

Licence - 3925



R1.9 A person who has been given written approval to certify a certificate of compliance under a licence issued under the Pollution Control Act 1970 is taken to be approved for the purpose of this condition until the date of first review of this licence.

R2 Notification of environmental harm

- Note: The licensee or its employees must notify the EPA of incidents causing or threatening material harm to the environment as soon as practicable after the person becomes aware of the incident in accordance with the requirements of Part 5.7 of the Act.
- R2.1 Notifications must be made by telephoning the Environment Line service on 131 555.
- R2.2 The licensee must provide written details of the notification to the EPA within 7 days of the date on which the incident occurred.

R3 Written report

- R3.1 Where an authorised officer of the EPA suspects on reasonable grounds that:
 - (a) where this licence applies to premises, an event has occurred at the premises; or
 - (b) where this licence applies to vehicles or mobile plant, an event has occurred in connection with the carrying out of the activities authorised by this licence,

and the event has caused, is causing or is likely to cause material harm to the environment (whether the harm occurs on or off premises to which the licence applies), the authorised officer may request a written report of the event.

- R3.2 The licensee must make all reasonable inquiries in relation to the event and supply the report to the EPA within such time as may be specified in the request.
- R3.3 The request may require a report which includes any or all of the following information:
 - (a) the cause, time and duration of the event;
 - (b) the type, volume and concentration of every pollutant discharged as a result of the event;
 - (c) the name, address and business hours telephone number of employees or agents of the licensee, or a specified class of them, who witnessed the event;
 - (d) the name, address and business hours telephone number of every other person (of whom the licensee is aware) who witnessed the event, unless the licensee has been unable to obtain that information after making reasonable effort;
 - (e) action taken by the licensee in relation to the event, including any follow-up contact with any complainants;
 - (f) details of any measure taken or proposed to be taken to prevent or mitigate against a recurrence of such an event; and
 - (g) any other relevant matters.
- R3.4 The EPA may make a written request for further details in relation to any of the above matters if it is not satisfied with the report provided by the licensee. The licensee must provide such further details to the EPA within the time specified in the request.

Licence - 3925



R4 Notification of bypass or overflow incidents

- R4.1 Where either:
 - (a) sewage or partially treated sewage is discharged from the premises as a result of a bypass of the sewage treatment plant, or:
 - (b) an observed or reported overflow has occurred from the reticulation system, and overflow or bypass may pose a risk to public health, the licensee is to promptly give appropriate notification to any parties that are likely to be affected, including:
 - (i) the potentially affected community;
 - (ii) the Department of Health;
 - (iii) Broken Hill City Council.
- R4.2 When the licensee notifies the Department of Health or Safe Food NSW Shellfish Quality Assurance Program of a bypass or overflow incident, the licensee must also notify the EPA by telephoning its Pollution Line service on 131 555. Notifications are to be given as soon as practicable after the licensee or one of the licensee's employees or agents becomes aware of the incident, and must include all relevant information including the information required under condition M9.1 or M7.1.

R5 Annual System Performance Report

- R5.1 The licensee must supply to the EPA an Annual System Performance Report not later than 60 days after the end of each reporting period.
- R5.2 The report is to supplement the Annual Return and must include but need not be limited to:
 - (a) the 50 percentile, 90 percentile, 100 percentile and 3DGM values calculated from the monitoring data required by this licence for the reporting period for each pollutant which has corresponding concentration limits specified in this licence;
 - (b) the total amounts of biosolids, as classified in the Biosolids Guideline, disposed of on-site, offsite and to landfill during the reporting period;
 - (c) a diagram showing the major process elements, discharge points and monitoring points at the premises' sewage treatment plant(s), where there has been any significant change since the previous reporting period or this information has not been provided previously to the EPA;
 - (d) the number of dry and wet weather bypasses recorded over the reporting period (recorded in accordance with condition M7);
 - (e) a breakdown of the total number of complaints received by the licensee during the reporting period in relation to the premises into categories of "odours – sewage treatment plant", "odours – reticulation system", "water pollution – sewage treatment plant", "water pollution – reticulation system" and any other category indicated by the complaints;
 - (f) a summary of observed, reported or recorded wet weather overflows and observed, reported or recorded dry weather overflows and sewage treatment plant bypasses. These data are to be for the current reporting period and for the four previous twelve-month periods, for which data has been collected. Any significant actions taken to address bypasses or overflows are to be noted;

Licence - 3925



- (g) the amount of rainfall measured at a rain gauge at the STP, or at the rain gauge closest to the centre of the catchment of the sewage treatment system, for each month of the reporting period; and
- (h) a brief progress report on the implementation over the reporting period of actions specified in PRP100.
- R5.3 The Annual System Performance Report must be presented in a format approved in writing by the EPA.
- R5.4 The requirements of R5.2 (d), (e), (f) and (g) apply to the part of the reporting period beginning three months after the date the licence is varied to include this condition.

General conditions

G1 Copy of licence kept at the premises

- G1.1 A copy of this licence must be kept at the premises to which the licence applies.
- G1.2 The licence must be produced to any authorised officer of the EPA who asks to see it.
- G1.3 The licence must be available for inspection by any employee or agent of the licensee working at the premises.
- Note: For the purposes of this condition, "the premises" refers to each Sewage Treatment Plant(s) described in condition A2.1.

G2 Signage

(b)

G2.1 The location of EPA point number(s) 2, 3, 6 and 10 must be clearly marked by signs that indicate the point identification number used in this licence and be located as close as practical to the point.

G3 Contact number for incidents and responsible employees

- G3.1 The licensee must operate 24-hour telephone contact lines for the purpose of enabling the EPA to directly contact one or more representatives of the licensee who can:
 - (a) respond at all times to incidents relating to the premises; and
 - contact the licensee's senior employees or agents authorised at all times to:
 - (i) speak on behalf of the licensee; and
 - (ii) provide any information or document required under this licence.



Licence - 3925

G3.2 The licensee is to inform the EPA in writing of the appointment of any subsequent contact persons, or changes to the person's contact details as soon as practicable and in any event within fourteen days of the appointment or change.

G4 Clean-up

G4.1 In the event of an overflow or bypass that harms or is likely to harm the environment, the licensee must use all practicable measures to minimise the impact of the overflow or bypass on the environment and public health. These measures are to be implemented as soon as practical after the licensee or one of the licensee's employees or agents becomes aware of the overflow or bypass.

Pollution studies and reduction programs

U1.1 Not applicable.

Special conditions

E1.1 Not applicable.

Dictionary

General Dictionary

In this licence, unless the contrary is indicated, the terms below have the following meanings:

3DGM [in relation to a concentration limit]	Means the three day geometric mean, which is calculated by multiplying the results of the analysis of three samples collected on consecutive days and then taking the cubed root of that amount. Where one or more of the samples is zero or below the detection limit for the analysis, then 1 or the detection limit respectively should be used in place of those samples
Act	Means the Protection of the Environment Operations Act 1997
activity	Means a scheduled or non-scheduled activity within the meaning of the Protection of the Environment Operations Act 1997
actual load	Has the same meaning as in the Protection of the Environment Operations (General) Regulation 1998
АМ	Together with a number, means an ambient air monitoring method of that number prescribed by the

Licence - 3925

Environment Protection Licence



	Approved Methods for the Sampling and Analysis of Air Pollutants in New South Wales.
AMG	Australian Map Grid
anniversary date	The anniversary date is the anniversary each year of the date of issue of the licence. In the case of a licence continued in force by the Protection of the Environment Operations Act 1997, the date of issue of the licence is the first anniversary of the date of issue or last renewal of the licence following the commencement of the Act.
annual return	Is defined in R1.1
Approved Methods Publication	Has the same meaning as in the Protection of the Environment Operations (General) Regulation 1998
assessable pollutants	Has the same meaning as in the Protection of the Environment Operations (General) Regulation 1998
BOD	Means biochemical oxygen demand
CEM	Together with a number, means a continuous emission monitoring method of that number prescribed by the Approved Methods for the Sampling and Analysis of Air Pollutants in New South Wales.
COD	Means chemical oxygen demand
composite sample	Unless otherwise specifically approved in writing by the EPA, a sample consisting of 24 individual samples collected at hourly intervals and each having an equivalent volume.
cond.	Means conductivity
environment	Has the same meaning as in the Protection of the Environment Operations Act 1997
environment protection legislation	Has the same meaning as in the Protection of the Environment Administration Act 1991
EPA	Means Environment Protection Authority of New South Wales.
fee-based activity classification	Means the numbered short descriptions in Schedule 1 of the Protection of the Environment Operations (General) Regulation 1998.
flow weighted composite sample	Means a sample whose composites are sized in proportion to the flow at each composites time of collection.
general solid waste (non-putrescible)	Has the same meaning as in Part 3 of Schedule 1 of the Protection of the Environment Operations Act 1997
general solid waste (putrescible)	Has the same meaning as in Part 3 of Schedule 1 of the Protection of the Environment Operations Act 1997
grab sample	Means a single sample taken at a point at a single time
hazardous waste	Has the same meaning as in Part 3 of Schedule 1 of the Protection of the Environment Operations Act 1997
licensee	Means the licence holder described at the front of this licence
load calculation protocol	Has the same meaning as in the Protection of the Environment Operations (General) Regulation 1998
local authority	Has the same meaning as in the Protection of the Environment Operations Act 1997
material harm	Has the same meaning as in section 147 Protection of the Environment Operations Act 1997
MBAS	Means methylene blue active substances

Licence - 3925



Minister	Means the Minister administering the Protection of the Environment Operations Act 1997
mobile plant	Has the same meaning as in Part 3 of Schedule 1 of the Protection of the Environment Operations Act 1997
motor vehicle	Has the same meaning as in the Protection of the Environment Operations Act 1997
O&G	Means oil and grease
percentile [in relation to a concentration limit of a sample]	Means that percentage [eg.50%] of the number of samples taken that must meet the concentration limit specified in the licence for that pollutant over a specified period of time. In this licence, the specified period of time is the Reporting Period unless otherwise stated in this licence.
plant	Includes all plant within the meaning of the Protection of the Environment Operations Act 1997 as well as motor vehicles.
pollution of waters [or water pollution]	Has the same meaning as in the Protection of the Environment Operations Act 1997
premises	Means the premises described in condition A2.1
public authority	Has the same meaning as in the Protection of the Environment Operations Act 1997
regional office	Means the relevant EPA office referred to in the Contacting the EPA document accompanying this licence
reporting period	For the purposes of this licence, the reporting period means the period of 12 months after the issue of the licence, and each subsequent period of 12 months. In the case of a licence continued in force by the Protection of the Environment Operations Act 1997, the date of issue of the licence is the first anniversary of the date of issue or last renewal of the licence following the commencement of the Act.
restricted solid waste	Has the same meaning as in Part 3 of Schedule 1 of the Protection of the Environment Operations Act 1997
scheduled activity	Means an activity listed in Schedule 1 of the Protection of the Environment Operations Act 1997
special waste	Has the same meaning as in Part 3 of Schedule 1 of the Protection of the Environment Operations Act 1997
тм	Together with a number, means a test method of that number prescribed by the Approved Methods for the Sampling and Analysis of Air Pollutants in New South Wales.
TSP	Means total suspended particles
TSS	Means total suspended solids
Type 1 substance	Means the elements antimony, arsenic, cadmium, lead or mercury or any compound containing one or more of those elements
Type 2 substance	Means the elements beryllium, chromium, cobalt, manganese, nickel, selenium, tin or vanadium or any compound containing one or more of those elements
utilisation area	Means any area shown as a utilisation area on a map submitted with the application for this licence
waste	Has the same meaning as in the Protection of the Environment Operations Act 1997
waste type	Means liquid, restricted solid waste, general solid waste (putrescible), general solid waste (non- putrescible), special waste or hazardous waste

Special Dictionary

Licence - 3925



ug/L	Means micrograms per litre.
access chamber	a structure constructed to provide physical access to sewer pipes. Also known as a manhole.
approved	Means approved in writing by the EPA. The EPA's approval may be given unconditionally, or subject to conditions.
Biosolids	Has the same meaning as in Schedule 1, Part 3 of the Protection of the Environment Operations Act 1997.
Biosolids Guidelines	Means the "Environmental Guidelines: Use and disposal of biosolids products" published by the EPA in October 1997, or any subsequently updated guidelines which replace this publication.
bypass	Means circumstances where sewage has been received at the sewage treatment plant but is discharged from the plant without it being treated, processed or reprocessed by means of any or all of the designed treatment processes of the plant. A new bypass event is defined as a bypass that commences at least 24 hours after the end of the previous bypass.
cfu	Means colony forming units
condition	Means a condition of this licence.
designed overflow structure	Means a designed structure (excluding access chambers) in the reticulation system which operates as a relief to allow sewage to discharge at a planned location or a sewage pumping station, but does not include a bypass from a sewage treatment plant.
designed overflow	Means an overflow from a designed overflow structure.
dry weather bypass	Means a bypass that occurs when the flow rate of sewage at the inflow point of the STP does not exceed the flow rate specified in M7.2.
dry weather overflow	Means an overflow that is not a wet weather overflow.
dry weather sewage treatment plant discharge	Means a discharge of sewage or effluent from the STP that occurs when the flow rate of sewage at the inflow point of the STP does not exceed the flow rate specified in M7.2
effluent	Means sewage that has received all of the designed treatment processes at the sewage treatment plant.
fc	Means faecal coliforms expressed in colony forming units per 100mL.
Group C waste	Has the same meaning as in Part 3 of Schedule 1 of the <i>Protection of the Environment Operations Act</i> 1997.
ISO	Means International Standards Organisation.
kL	Means kilolitre.
L/s	Means litres per second.
metal-A	Means the following metals: arsenic, cadmium, chromium, copper, lead, mercury, nickel, selenium, silver and zinc.
mL	Means millilitres.
ML	Means megalitres.
offensive odour	Has the same meaning as in the Protection of the Environment Operations Act 1997.
overflow	Is a discharge of untreated or partially treated sewage from the sewage treatment system.



Licence - 3925

reticulation system	Means that part of the sewage treatment system owned and operated by the licensee which collects and transports sewage to the sewage treatment plant and includes all sewer pipes (whether greater or less than 300mm diameter), sewer rising mains, access chambers, vent shafts, designed overflow structures, sewage ejection units and sewage pumping stations, but does not include the sewage treatment plant.
sewage	Means untreated liquid waste received in the reticulation system.
sewage ejection unit	Is a pump intended to control the transport of sewage from premises normally occupied by no more than 10 persons, or of an average daily flow of sewage not exceeding 2,000 litres through the sewer pipes, where steep hills and other variations in the land topography can prevent or limit the gravity flow of sewage to the sewage treatment plant.
sewage products	Means any by-product of the treatment processes and includes biosolids, raw sludge, liquid sludge, thickened sludge, digested sludge, screenings and grit.
sewage pumping station (SPS)	Is a structure which controls the transport of sewage through the sewer pipes, where steep hills and other variations in the land topography can prevent or limit the gravity flow of sewage to the sewage treatment plant, but does not include a sewage ejection unit.
sewage treatment plant (STP)	Is a facility at which sewage is stored and treated following delivery from the reticulation system prior to discharge, and includes discharge structures and STP bypass points.
sewage treatment system	Means the reticulation system and the sewage treatment plant used for the transport, treatment and discharge of effluent and sewage.
Trade waste agreements	Means agreements reached between the licensee and industrial and commercial customers to restrict the amount of toxic and other potentially harmful substances discharged to the reticulation system.
TRC	Means total residual chlorine.
waters	Has the same meaning as in the Protection of the Environment Operations Act 1997.
wet weather bypass	Means a bypass that occurs when the flow rate of sewage at the inflow point of the STP equals or exceeds the rate specified in condition M7.2.
wet weather overflow	A wet weather overflow is an overflow where the probable cause is rainfall.

Mr Terry Knowles

Environment Protection Authority

(By Delegation)

Date of this edition - 07-Jun-2010

Licence - 3925

End Notes



Licence varied by notice V/M Upgrade, issued on 07-Jul-2000, which came into effect on 1 07-Jul-2000. Licence transferred through application 140921, approved on 20-Nov-2001, which came into 2 effect on 01-Jan-2000. Licence varied by notice 1013845, issued on 09-Jan-2002, which came into effect on 3 23-Jan-2002. Licence varied by notice 1016965, issued on 11-Jun-2002, which came into effect on 4 06-Jul-2002. Licence varied by notice 1029459, issued on 20-Aug-2003, which came into effect on 5 14-Sep-2003. Licence varied by notice 1039363, issued on 12-Aug-2004, which came into effect on 6 06-Sep-2004. 7 EPA Condition ID S40934 amended 13-08-04 Licence varied by notice 1045292, issued on 07-Apr-2005, which came into effect on 8 02-May-2005. Licence varied by notice 1047540, issued on 09-Jun-2005, which came into effect on 9 04-Jul-2005. Licence varied by notice 1056087, issued on 13-Feb-2006, which came into effect on 10 10-Mar-2006. Licence varied by notice 1060913, issued on 09-Jun-2006, which came into effect on 11 09-Jun-2006. Licence varied by notice 1076145, issued on 18-Jul-2007, which came into effect on 12 18-Jul-2007. Condition A1.3 Not applicable varied by notice issued on <issue date> which came into 13 effect on <effective date> Licence varied by notice 1114485, issued on 07-Jun-2010, which came into effect on 14 07-Jun-2010.